



## 140MT MPCBs and MCPs

[140MT-C3E-B40](#)

MPCB, Standard Magnetic Trip (Fixed at 14 x Ie), 2.5 - 4 A, Std. Performance, Frame Size C

### Product Details

| SYSTEM VOLTAGE DATA                              |   |
|--|---|
| Supply Voltage                                   | 480V 60Hz                                 |
| Maximum Available Fault Current (at the Breaker) | 0 kA                                      |
| CIRCUIT BREAKER                                  |   |
| Circuit Breaker Type                             | Motor Protection Circuit Breaker          |
| Adj. Thermal Current Range (A)                   | 2.5 - 4A                                  |
| Frame Size                                       | Frame Size C                              |
| Breaking Capacity                                | Standard Breaking Capacity                |
| Application                                      | Standard Magnetic Trip (Fixed at 14 x Ie) |
| ASSEMBLY   |   |
| Factory or User Assembled?                       | Factory Assembled                         |
| OPTIONS  |   |
| Side Mount Shunt Trip and Undervoltage Release   | None                                      |
| Front Mount Auxiliary and Trip Contacts          | None                                      |
| Side Mount Auxiliary and Trip Contacts           | None                                      |

### Supporting Documentation and Downloads

- [Installation Instructions](#)