

P/N: MR40

Copyright

© 2017, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: MR40

Release:

Commit: 41014

Language:

Modified: 2017-03-09

Formatted: 2017-03-09

Website

<http://www.flir.com>

Customer support

<http://support.flir.com>

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.



Part number	MR40
Part name	Moisture Pen + Flashlight
Part description	<p>The FLIR MR40 is a rugged 2-pin, single-scale moisture meter with an integrated flashlight for wood and common building materials—ideal for builders, building inspectors, remodelers, moisture remediation technicians, pest control professionals, and residential roofing and flooring contractors. Providing reliable and accurate measurements at a highly affordable price point, the FLIR MR40 is a quick and easy-to-use tool to find and quantify moisture problems. With its pen-like form factor, the FLIR MR40 can be carried in a shirt pocket, ready to work.</p> <ul style="list-style-type: none"> • Sleek design for getting into corners. • Replaceable pins—spare set included. • Measurement “hold” function. • Lanyard cap retention.
Measurement	
Measurement range	5–60% MC (moisture content)
Measurement accuracy	<ul style="list-style-type: none"> • 5–30 ± 2% MC • 30–60% MC: reference only <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>NOTE</p> <p>The displayed reading is for Group 9/Building materials, including plywood, drywall, and oriented-strand board. For other materials, refer to the conversion chart available on the FLIR customer support website: http://tinyurl.com/jteb653</p> </div>
Audible indication	5–12%: low beep rate. 13–60%: higher beep rate. >60%: highest beep rate (display OL)
Calibration/pin check, integrated in cap	16%
Meter data	
Work light	~40 lumens
Display	LCD
Electrode pins	Integrated, replaceable
Measurement principle	Electrical resistance
Warranty	Limited lifetime
Calibration cycle	N/A
Certifications	
Certifications	CE



FLIR MR40

P/N: MR40

© 2017, FLIR Systems, Inc.
#MR40; r. /41014;

Power system	
Power requirements	2 × AAA alkaline batteries
Battery life	70 hours without flashlight
Battery status indicator	4-bar battery icon
Auto power off (APO)	3 minutes

Environmental data	
Drop test	3 m (9.8 ft.)
Ingress protection rating	IP54 splash proof
Operating temperature	-10 to +60°C (14-140°F)

Physical data	
Weight	80 g (2.8 oz) with battery
Dimensions (H × W × L)	193 mm × 26 mm × 31 mm (7.6 in. × 1.0 in. × 1.2 in.)
Material	PC-ABS with TPE overmold
Color	Gray and black

Shipping information	
Packaging type	Color box with view of product in clamshell
Packaging contents	<ul style="list-style-type: none">• MR40 Moisture Pen + Flashlight• 2 × AAA Energizer batteries• Spare pin set• User manual
Packaging weight	0.17 kg (0.38 lb.)
Packaging dimensions (H × W × L)	24.5 cm × 8.5 cm × 6.5 cm (9.7 in. × 3.4 in. × 2.5 in.)
Carton weight	4.7 kg (10.3 lb.)
Carton dimensions (H × W × L)	47.7 cm × 37 cm × 20 cm (18.8 in. × 14.6 in. × 7.9 in.)
Carton quantity	20
EAN-13	0793950370414
UPC-12	793950370414
Country of origin	China
Tariff code	9025803500

Accessories	
MO25-PINS	Spare Electrode Pins (10 pins per pack)

Technical support	
Website	http://support.flir.com
E-mail	TMSupport@flir.com
Phone	855-499-3662
Repairs	repair@flir.com