

FREE-STAND SINGLE OR DUAL ACCESS TYPE 12



Available with front or front and rear access, these Type 12 enclosures have sturdy unibody construction and flexible internal mounting options to provide panel and component mounting flexibility

FEATURES & BENEFITS

Seams continuously welded and ground smooth; no holes or knockouts

Stiffeners on back of two-door enclosures maintain flatness and increase rigidity

Lifting eyes for easy handling

3-point latches operated by oil-tight key-locking handle

Concealed, easy-to-remove hinges

Data pockets are high-impact thermoplastic

Internal mounting channels welded horizontally to sides at top, bottom and center

Optional panels and rack mount angles can be mounted anywhere along channels

Oil-resistant door gasket

Bonding provision on door

Provision for mounting fluorescent light

SPECIFICATIONS

Color Gray

Color Code ANSI 61

Finish Powder Coated

Interior Color Gray

Thickness 12 ga

Table 1/2

Catalog Number	Height	Width	Depth	Protection Rating	Material	Rack Unit Quantity
A722424FSDAG	72.06 in	24.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	35
A722430FSDAG	72.06 in	24.06 in	30.06 in	NEMA Type 12; IP55	Mild Steel	35
A722436FSDAG	72.06 in	24.06 in	36.06 in	NEMA Type 12; IP55	Mild Steel	35
A723024FSDAG	72.06 in	30.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	35
A723624FSDAG	72.06 in	36.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	35
A723636FSDAG	72.06 in	36.06 in	36.06 in	NEMA Type 12; IP55	Mild Steel	35
A724824FSDADG	72.06 in	48.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	35
A726024FSDADG	72.06 in	60.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	35
A726036FSDADG	72.06 in	60.06 in	36.06 in	NEMA Type 12; IP55	Mild Steel	35
A727224FSDADG	72.06 in	72.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	35
A903624FSDAG	90.06 in	36.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	45
A903636FSDAG	90.06 in	36.06 in	36.06 in	NEMA Type 12; IP55	Mild Steel	45
A907224FSDADG	90.06 in	72.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	45
A602418FSG	60.06 in	24.06 in	18.06 in	NEMA Type 12; IP55	Mild Steel	28
A603624FSG	60.06 in	36.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	28
A604818FSDG	60.06 in	48.06 in	18.06 in	NEMA Type 12; IP55	Mild Steel	28
A722418FSG	72.06 in	24.06 in	18.06 in	NEMA Type 12; IP55	Mild Steel	35
A722424FSG	72.06 in	24.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	35
A723018FSG	72.06 in	30.06 in	18.06 in	NEMA Type 12; IP55	Mild Steel	35
A723024FSG	72.06 in	30.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	35
A723618FSG	72.06 in	36.06 in	18.06 in	NEMA Type 12; IP55	Mild Steel	35
A723624FSG	72.06 in	36.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	35
A723630FSG	72.06 in	36.06 in	30.06 in	NEMA Type 12; IP55	Mild Steel	35
A723636FSG	72.06 in	36.06 in	36.06 in	NEMA Type 12; IP55	Mild Steel	35
A724818FSDG	72.06 in	48.06 in	18.06 in	NEMA Type 12; IP55	Mild Steel	35
A724824FSDG	72.06 in	48.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	35
A726018FSDG	72.06 in	60.06 in	18.06 in	NEMA Type 12; IP55	Mild Steel	35
A726024FSDG	72.06 in	60.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	35
A726036FSDG	72.06 in	60.06 in	36.06 in	NEMA Type 12; IP55	Mild Steel	35
A727218FSDG	72.06 in	72.06 in	18.06 in	NEMA Type 12; IP55	Mild Steel	35
A727224FSDG	72.06 in	72.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	35
A902420FSG	90.06 in	24.06 in	20.06 in	NEMA Type 12; IP55	Mild Steel	45
A903620FSG	90.06 in	36.06 in	20.06 in	NEMA Type 12; IP55	Mild Steel	45

Catalog Number	Height	Width	Depth	Protection Rating	Material	Rack Unit Quantity
A903624FSG	90.06 in	36.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	45
A903636FSG	90.06 in	36.06 in	36.06 in	NEMA Type 12; IP55	Mild Steel	45
A904820FSDG	90.06 in	48.06 in	20.06 in	NEMA Type 12; IP55	Mild Steel	45
A907220FSDG	90.06 in	72.06 in	20.06 in	NEMA Type 12; IP55	Mild Steel	45
A907224FSDG	90.06 in	72.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	45
A907236FSDG	90.06 in	72.06 in	36.06 in	NEMA Type 12; IP55	Mild Steel	45

Table 2/2

Catalog Number	Lifting Eye Quantity
A722424FSDAG	2
A722430FSDAG	4
A722436FSDAG	4
A723024FSDAG	2
A723624FSDAG	2
A723636FSDAG	4
A724824FSDADG	2
A726024FSDADG	2
A726036FSDADG	4
A727224FSDADG	2
A903624FSDAG	2
A903636FSDAG	4
A907224FSDADG	2
A602418FSG	2
A603624FSG	2
A604818FSDG	2
A722418FSG	2
A722424FSG	2
A723018FSG	2
A723024FSG	2
A723618FSG	2
A723624FSG	2
A723630FSG	4
A723636FSG	4
A724818FSDG	2

Catalog Number	Lifting Eye Quantity
A724824FSDG	2
A726018FSDG	2
A726024FSDG	2
A726036FSDG	4
A727218FSDG	2
A727224FSDG	2
A902420FSG	2
A903620FSG	2
A903624FSG	2
A903636FSG	4
A904820FSDG	2
A907220FSDG	2
A907224FSDG	2
A907236FSDG	4

Color Gray

Color Code ANSI 61

Finish Powder Coated

Interior Color Gray

Thickness 12 ga

Table 1/2

Catalog Number	Height	Width	Depth	Protection Rating	Material	Rack Unit Quantity
A722424FSDAG	72.06 in	24.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	35
A722430FSDAG	72.06 in	24.06 in	30.06 in	NEMA Type 12; IP55	Mild Steel	35
A722436FSDAG	72.06 in	24.06 in	36.06 in	NEMA Type 12; IP55	Mild Steel	35
A723024FSDAG	72.06 in	30.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	35
A723624FSDAG	72.06 in	36.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	35
A723636FSDAG	72.06 in	36.06 in	36.06 in	NEMA Type 12; IP55	Mild Steel	35
A724824FSDADG	72.06 in	48.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	35
A726024FSDADG	72.06 in	60.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	35
A726036FSDADG	72.06 in	60.06 in	36.06 in	NEMA Type 12; IP55	Mild Steel	35
A727224FSDADG	72.06 in	72.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	35

Catalog Number	Height	Width	Depth	Protection Rating	Material	Rack Unit Quantity
A903624FSDAG	90.06 in	36.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	45
A903636FSDAG	90.06 in	36.06 in	36.06 in	NEMA Type 12; IP55	Mild Steel	45
A907224FSDADG	90.06 in	72.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	45
A602418FSG	60.06 in	24.06 in	18.06 in	NEMA Type 12; IP55	Mild Steel	28
A603624FSG	60.06 in	36.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	28
A604818FSDG	60.06 in	48.06 in	18.06 in	NEMA Type 12; IP55	Mild Steel	28
A722418FSG	72.06 in	24.06 in	18.06 in	NEMA Type 12; IP55	Mild Steel	35
A722424FSG	72.06 in	24.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	35
A723018FSG	72.06 in	30.06 in	18.06 in	NEMA Type 12; IP55	Mild Steel	35
A723024FSG	72.06 in	30.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	35
A723618FSG	72.06 in	36.06 in	18.06 in	NEMA Type 12; IP55	Mild Steel	35
A723624FSG	72.06 in	36.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	35
A723630FSG	72.06 in	36.06 in	30.06 in	NEMA Type 12; IP55	Mild Steel	35
A723636FSG	72.06 in	36.06 in	36.06 in	NEMA Type 12; IP55	Mild Steel	35
A724818FSDG	72.06 in	48.06 in	18.06 in	NEMA Type 12; IP55	Mild Steel	35
A724824FSDG	72.06 in	48.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	35
A726018FSDG	72.06 in	60.06 in	18.06 in	NEMA Type 12; IP55	Mild Steel	35
A726024FSDG	72.06 in	60.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	35
A726036FSDG	72.06 in	60.06 in	36.06 in	NEMA Type 12; IP55	Mild Steel	35
A727218FSDG	72.06 in	72.06 in	18.06 in	NEMA Type 12; IP55	Mild Steel	35
A727224FSDG	72.06 in	72.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	35
A902420FSG	90.06 in	24.06 in	20.06 in	NEMA Type 12; IP55	Mild Steel	45
A903620FSG	90.06 in	36.06 in	20.06 in	NEMA Type 12; IP55	Mild Steel	45
A903624FSG	90.06 in	36.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	45
A903636FSG	90.06 in	36.06 in	36.06 in	NEMA Type 12; IP55	Mild Steel	45
A904820FSDG	90.06 in	48.06 in	20.06 in	NEMA Type 12; IP55	Mild Steel	45
A907220FSDG	90.06 in	72.06 in	20.06 in	NEMA Type 12; IP55	Mild Steel	45
A907224FSDG	90.06 in	72.06 in	24.06 in	NEMA Type 12; IP55	Mild Steel	45
A907236FSDG	90.06 in	72.06 in	36.06 in	NEMA Type 12; IP55	Mild Steel	45

Table 2/2

Catalog Number	Lifting Eye Quantity
A722424FSDAG	2
A722430FSDAG	4

Catalog Number	Lifting Eye Quantity
A722436FSDAG	4
A723024FSDAG	2
A723624FSDAG	2
A723636FSDAG	4
A724824FSDADG	2
A726024FSDADG	2
A726036FSDADG	4
A727224FSDADG	2
A903624FSDAG	2
A903636FSDAG	4
A907224FSDADG	2
A602418FSG	2
A603624FSG	2
A604818FSDG	2
A722418FSG	2
A722424FSG	2
A723018FSG	2
A723024FSG	2
A723618FSG	2
A723624FSG	2
A723630FSG	4
A723636FSG	4
A724818FSDG	2
A724824FSDG	2
A726018FSDG	2
A726024FSDG	2
A726036FSDG	4
A727218FSDG	2
A727224FSDG	2
A902420FSG	2
A903620FSG	2
A903624FSG	2
A903636FSG	4

Catalog Number	Lifting Eye Quantity
A904820FSDG	2
A907220FSDG	2
A907224FSDG	2
A907236FSDG	4

Order panels separately.

Four lifting eyes are furnished if C = 30.06 (764mm) or more. Removable 12.00 x 12.00 (305mm x 305mm) data pocket included.

2100 Hoffman Way
 Anoka, MN 55303-1745 | USA
 763.421.2240



Our powerful portfolio of brands:
 nVent.com **CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER**

© 2023 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.