

Product data sheet

Specifications



RACK PDU, BASIC, 0U/1U, 120-240V/15A, 220-240V/10A, (8) C13

AP6015A

Overview

Lead time Usually in Stock

Main

Main Input Voltage 100 V
120 V
200 V
208 V
230 V
240 V

PDU Type Basic

Main Output Voltage 100 V
120 V
200 V
208 V
230 V
240 V

Input Connection Type IEC 60320 C14

Number of rack unit 1U

Provided Equipment Installation guide
Safety guide

Physical

Color Black

Height 9.45 in (24 cm)

Width 1.73 in (4.4 cm)

Depth 3.66 in (9.3 cm)

Net Weight 2.01 lb(US) (0.91 kg)

Mounting Location Front
Rear

Mounting preference No preference

Mounting Mode Not rack-mountable

Input

Line Rated Current 12 A

Acceptable Input Voltage 100...240 V

Max line current 15 A

Input current limits	15 A
Load Capacity	2300 VA
Input Frequency	50/60 Hz

Output

Number of power socket outlets	8 IEC 60320 C13
---------------------------------------	-----------------

Conformance

Product Certifications	cUL Listed CE EAC IRAM UL Listed VDE
-------------------------------	---

Ordering and shipping details

GTIN	731304327790
-------------	--------------

Packing Units

Unit Type of Package 1	Db
Number of Units in Package 1	1
Package 1 Height	11.26 in (28.6 cm)
Package 1 Width	5.12 in (13 cm)
Package 1 Length	8.27 in (21 cm)
Package 1 Weight	3.02 lb(US) (1.37 kg)
SCC14	10731304327797

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------

Recommended replacement(s)