

PRODUCT-DETAILS

CAL18-11

CAL18-11 Auxiliary Contact Block



General Information

| | |
|-----------------------|--|
| Extended Product Type | CAL18-11 |
| Product ID | 1SFN010720R1011 |
| EAN | 7320500256305 |
| Catalog Description | CAL18-11 Auxiliary Contact Block |
| Long Description | 2 pole screw type side mounted auxilliary contact block, instantaneous N.O. and N.C. contacts, suitable for standard industrial environments |

Ordering

| | |
|------------------------|----------|
| Minimum Order Quantity | 2 piece |
| Customs Tariff Number | 85369010 |
| Product Main Type | CAL18 |

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SBC100122C0202 |
| Instructions and Manuals | 1SFC101009M5501 |
| CAD Dimensional Drawing | 2CDC001079B0201 |

Dimensions

| | |
|----------------------------|---------|
| Product Net Width | 64.5 mm |
| Product Net Depth / Length | 17.1 mm |
| Product Net Height | 74 mm |
| Product Net Weight | 0.04 kg |

Technical

| | |
|---------------------------------------|--|
| Connecting Capacity Auxiliary Circuit | Flexible with Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Ferrule 2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm ² Solid 1x 1 ... 4 mm ² Solid 2x 1 ... 4 mm ² |
| Number of Auxiliary Contacts NC | 1 |
| Number of Auxiliary Contacts NO | 1 |
| Power Loss | at Rated Operating Conditions per Pole 0.15 W |
| Rated Operational Voltage | Auxiliary Circuit 24 ... 690 V |
| Recommended Screw Driver | Auxiliary Circuit 1 x 5.5 Auxiliary Circuit Pozidriv 2 |
| Suitable For | AF400 AF460 AF580 AF750 AF1250 AF1350 AF1650 AF2050 AF2650 AF2850 AF95B GAF185 GAF300 GAF460 GAF750 GAF1250 GAF1650 GAF2050 A95 A110 A145 A185 A210 A260 A300 UA95 UA110 AF95 AF110 AF145 AF185 AF210 AF260 AF300 |
| Suitable for Product Class | Block Contactors |
| Terminal Type | Screw Terminals |
| Tightening Torque | Auxiliary Circuit 1 N·m |
| Wire Stripping Length | Auxiliary Circuit 9 mm |

Environmental

| | |
|----------------------|-----------------|
| Degree of Protection | IP20 |
| RoHS Information | 2CMT2021-006277 |

WEEE B2C / B2B

Business To Business

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations (Document Number)

| | |
|-------------------------------------|--|
| CB Certificate | SE-85989 |
| CQC Certificate | CQC2003010304088244 CQC2009010304365509 |
| Declaration of Conformity - CCC | 2020980304001307 2020980304001060 |
| Declaration of Conformity - CE | 2CMT2015-005448 |
| Declaration of Conformity - UKCA | 2CMT2020-006119 |
| Instructions and Manuals | 1SFC101009M5501 |
| REACH Declaration | 2CMT2021-006202 |
| RoHS Information | 2CMT2021-006277 |
| UL Certificate | 20160916-E76003 |

Container Information

| | |
|-----------------------------------|---------------|
| Package Level 1 Units | bag 1 piece |
| Package Level 1 Width | 64.5 mm |
| Package Level 1 Depth / Length | 74 mm |
| Package Level 1 Height | 17.1 mm |
| Package Level 1 Gross Weight | 0.05 kg |
| Package Level 1 EAN | 7320500256305 |

Classifications

| | |
|---------------------------------------|--|
| eClass | V11.0 : 27371003 |
| E-Number (Finland) | 3709263 |
| E-Number (Norway) | 4116022 |
| E-Number (Sweden) | 3228821 |
| ETIM 6 | EC000041 - Auxiliary contact block |
| ETIM 7 | EC000041 - Auxiliary contact block |
| ETIM 8 | EC000041 - Auxiliary contact block |
| ETIM 9 | EC000066 - Power contactor, AC switching |
| IDEA Granular Category Code (IGCC) | 4743 >> Auxiliary contact block |
| Object Classification Code | K |
| UNSPSC | 39121529 |

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors Accessories

